

HYDRAULIC

422



Parker's worldwide hose line is designed to accommodate global customer requirements. Manufactured to strict international specifications, 422 hose offers customers consistency of performance combined with improved availability anywhere in the world.

- One-wire braid hose design manufactured to international specifications (ISO 1436-1 Type 1SN)
- Increased working pressures for improved reliability and expanded applications versus standard SAE 100R1
- Synthetic rubber inner tube for greater fluid compatibility and bio-oil resistance
- EN853 Type 1SN



**422**  
**Hydraulic Worldwide**

ISO 1436-1 TYPE 1SN/SAE 100R1 TYPE AT, J1942 / EN 853 TYPE 1SN / USCG HF / DNV / ABS

**Application:** Petroleum base hydraulic fluids and lubricating oils.  
**Inner Tube:** Synthetic rubber.  
**Reinforcement:** One braid steel wire.  
**Cover:** Synthetic rubber.  
**Temperature Range:** -40°F to +212°F (-40°C to +100°C).  
**Fittings:** 43 Series - pg. B-27.  
 42 Series - pg. B-173.

# Part Number	Hose I.D.		Hose O.D.		Working Pressure		Minimum Bend Radius		Weight		Vacuum Rating		Parkrimp	Field Attachable
	inch	mm	inch	mm	psi	MPa	inch	mm	lbs/ft	kg/m	of Hg	kPa	43 Series	42 Series
422-4	1/4	6,3	0.53	13	3250	22,5	4	100	0.16	0,24	24	81	●	●
422-5	5/16	6,3	0.59	15	3125	21,5	4-1/2	115	0.18	0,27	24	81	●	●
422-6	3/8	10	0.68	17	2600	18,0	5	130	0.23	0,34	24	81	●	●
422-8	1/2	12,5	0.81	21	2325	16,0	7	180	0.29	0,43	24	81	●	●
422-10	5/8	16	0.94	24	1875	13,0	8	200	0.33	0,49	24	81	●	●
422-12	3/4	19	1.09	28	1525	10,5	9-1/2	240	0.42	0,63	24	81	●	●
422-16	1	25	1.41	36	1275	8,8	12	300	0.63	0,94	24	81	●	●
422-20	1-1/4	31,5	1.79	45	900	6,3	16-1/2	420	0.8	1,19	18	61	●	●
422-24	1-1/2	38	2	51	725	5,0	20	500	1	1,49	18	61	●	●
422-32	2	51	2.54	64	575	4,0	25	630	1.5	2,24	18	61	●	●

- Field Attachable Assembly Instructions are in Section B with each Fittings Series.
- See Section C for Parkrimp Assembly Instructions.
- Temperature Range of other media listed in Section E.