

FlexiPanels® - FP3

High performance low cost HMIs




- Great value in a high quality color display!
- 3.5" to 10.2" TFT color display with touch screen
- Slim design - minimal space behind the panel is required
- Two serial communication interfaces (one RS 232 and one RS 232/485)
- Optional Ethernet port
- One USB programming port
- One USB Host port for program downloads and data log uploads
- Supports horizontal and vertical display orientation
- Front panel mounting with IP 66 rating
- Multi language support with true type Windows fonts

Model Comparison

Models	FP3035T-24	FP3043T	FP3043TN	FP3070T	FP3070TN	FP3102T	FP3102TN
Display	3.5" HVGA Color TFT	4.3" WQVGA Color TFT	4.3" WQVGA Color TFT	7" WVGA Color TFT	7" WVGA Color TFT	10.2" WVGA Color TFT	10.2" WVGA Color TFT
Resolution	480x320 Pixels	480x272 Pixels	480x272 Pixels	800x480 Pixels	800x480 Pixels	800x480 Pixels	800x480 Pixels
Backlight	LED Backlight	LED Backlight	LED Backlight	LED Backlight	LED Backlight	LED Backlight	LED Backlight
CPU	32-bit RISC processor	32-bit RISC processor	32-bit RISC processor	32-bit RISC processor	32-bit RISC processor	32-bit RISC processor	32-bit RISC processor
Memory	Up to 16.5MB	Up to 30MB	Up to 30MB	Up to 30MB	Up to 30MB	Up to 30MB	Up to 30MB
Screen Memory	Up to 16MB	Up to 10MB	Up to 10MB	Up to 10MB	Up to 10MB	Up to 10MB	Up to 10MB
Historical Alarms	20 Alarms	2700 Alarms	2700 Alarms	2700 Alarms	2700 Alarms	2700 Alarms	2700 Alarms
Retentive Memory	1400 Words (EEPROM)	1400 Words (EEPROM)	1400 Words (EEPROM)	1400 Words (EEPROM)	1400 Words (EEPROM)	1400 Words (EEPROM)	1400 Words (EEPROM)
Data Log (Internal)	NA	Up to 20 MB	Up to 20 MB	Up to 20 MB	Up to 20 MB	Up to 20 MB	Up to 20 MB
Serial Communication							
Number of ports	2 [#]	2 [#]	2 [#]	2	2	2	2
Com1	RS232	RS232	RS232	RS232 / RS485	RS232 / RS485	RS232 / RS485	RS232 / RS485
Com2	RS485	RS485	RS485	RS232 / RS485	RS232 / RS485	RS232 / RS485	RS232 / RS485
USB Interfaces							
USB Device	1 USB Device Type B port for programming	1 USB Device Type B port for programming	1 USB Device Type B port for programming	1 USB Device Type B port for programming	1 USB Device Type B port for programming	1 USB Device Type B port for programming	1 USB Device Type B port for programming
USB Host	NA	1 USB Host port	1 USB Host port	1 USB Host port	1 USB Host port	1 USB Host port	1 USB Host port
Ethernet Interface	NA	NA	One 10/100 Mbps	NA	One 10/100 Mbps	NA	One 10/100 Mbps
RTC	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Power Supply	12/24VDC (± 10%)	12/24VDC (± 10%)	12/24VDC (± 10%)	12/24VDC (± 10%)	12/24VDC (± 10%)	12/24VDC (± 10%)	12/24VDC (± 10%)
Operating Temperature	0 to 60° C	0 to 60° C	0 to 60° C	0 to 60° C	0 to 60° C	0 to 60° C	0 to 60° C
Storage Temperature	-20 to 85° C	-20 to 85° C	-20 to 85° C	-20 to 85° C	-20 to 85° C	-20 to 85° C	-20 to 85° C
Humidity	10 to 85% non condensing	10 to 85% non condensing	10 to 85% non condensing	10 to 85% non condensing	10 to 85% non condensing	10 to 85% non condensing	10 to 85% non condensing
Approvals	CE, UL Class I Div 2	CE, UL Class I Div 2	CE, UL Class I Div 2	CE, UL Class I Div 2	CE, UL Class I Div 2	CE, UL Class I Div 2	CE, UL Class I Div 2
Mounting	Front Panel Mounting, IP66 rated	Front Panel Mounting, IP66 rated	Front Panel Mounting, IP66 rated	Front Panel Mounting, IP66 rated	Front Panel Mounting, IP66 rated	Front Panel Mounting, IP66 rated	Front Panel Mounting, IP66 rated
Dimensions (mm)	107W x 69H x 25D (Drawing A)	TBC	TBC	186W x138H x 31D (Drawing B)	186W x138H x 31D (Drawing B)	TBC	TBC

FP3035 and FP3043 support One DB9 port that supports RS232 and RS485 levels on different pins. "Y" type cable can be used for separate RS232 and RS485 levels simultaneously

HMI Software Features



Supported Objects

Drawing Tools	Advance Objects
□ Line, Rectangle, Ellipse	□ Buttons
□ Rounded Rectangle	□ Lamps
□ Text, Multilingual text	□ Bargraph
□ Picture	□ Multiple Bargraph
Data Entry / Data Display	□ Analog Meter
□ Numeric data	□ Alarm
□ Bit data	□ Numeric Keypad
Clock objects	□ ASCII Keypad
□ Time	□ Custom Keypad
□ Date	

Supported Tasks

Supported tasks
□ Button specific tasks
□ Global tasks
□ Screen specific tasks
□ Data exchange tasks


Protocols Supported Include

Driver	FP3 Series
ABB	✓
Allen Bradley DF1	✓
Aromat FP Series	✓
Baldor	✓
Danfoss Drive	✓
Delta	✓
Fatek	✓
GE Fanuc	✓
GE SNP-X	✓

Driver	FP3 Series
Idec	✓
LG Master K series	✓
LG Master-K 300S	✓
Mitsubishi FX	✓
Mitsubishi Q series (Serial)	✓
Modbus master	✓
Modbus slave	✓
Omron Host Link	✓
Omron Yaskawa Drive	✓


Driver	FP3 Series
Serial Monitor	✓
Siemens-S7-200	✓
Siemens-S7-300	✓
Toshiba Inverters	✓
Toshiba T1	✓
Toshiba T2 Link port	✓
Twido	✓
Unitelway	✓
Universal Serial (ASCII)	✓

Application Example




Dimensions

Drawing A



Drawing B



All dimensions are in mm.

Ordering Information

Models	Description
FP3035T-24	3.5" TFT, 12/24VDC, USB Device
FP3043T	4.3" TFT, 12/24VDC, USB Device
FP3043TN	4.3" TFT, 12/24VDC, USB Device, Ethernet
FP3070T	7" TFT, 12/24VDC, USB Device
FP3070TN	7" TFT, 12/24VDC, USB Device, Ethernet
FP3102T	10.2" TFT, 12/24VDC, USB Device
FP3102TN	10.2" TFT, 12/24VDC, USB Device, Ethernet