

Revised
March 19th,
2013



9411 Corsair Road
Frankfort IL 60423
(800) 552-0299 Phone
(815) 464-5650 Fax

EMERGENCY PHONE (800) 255-3924
MATERIAL SAFETY DATA SHEET
MP54750 / MP54750NS
PART A (RESIN)

HMIS	HEALTH 2	FLAMMABILITY 1	REACTIVITY 0
NFPA	HEALTH 2	FIRE HAZARD 1	REACTIVITY 0

1. Chemical Product

Product Name: MP54750 / MP54750NS PART A (RESIN)
Product Type: Epoxy Resin

2. Identity of Ingredients

Ingredients	CAS No.	OSHA PEL	ACGIH TLV	Other Limits	%Composition
Reaction product: bisphenol-A-(epichlorohydrin); epoxy resin (number average molecular weight <=700)	25068-38-6	N/A	N/A	N/A	100

3. Hazards Identification

Human health hazards: May be irritating to the eyes and skin. Contact with hot material can cause thermal burns. May cause skin sensitization.

Safety hazards: Material will not burn unless preheated.

4. First aid measures

Inhalation: Remove victim to fresh air and provide oxygen if breathing is difficult. Give artificial respiration if not breathing. Get medical attention.

Skin contact: In case of contact with hot product, immediately flood the affected area with cold water. Wipe excess material from exposed area. Flush exposed skin with water and follow by washing with soap if available. Carefully remove clothing; if clothing is stuck to a burn area do not pull it off, but cut around it. Cover burn area do not pull it off, but cut around it. Transport to nearest medical facility for additional treatment.

Eye contact: Flush eye with water. Rest eyes for 30 minutes. If symptoms persist, consult a physician.

Ingestion: Do not induce vomiting. Have victim rinse out mouth with water, then drink sips of water to remove taste from mouth. In general, no treatment is necessary unless large quantities are ingested. However, get medical advice. If vomiting occurs spontaneously, keep head below hips to prevent aspiration.

5. Fire fighting measures

Extinguishing media: Carbon dioxide, dry chemical, foam, or water fog.

Specific hazards during fire fighting: Material will not burn unless preheated. Cool fire exposed containers with water.

Special protective equipment for fire fighters: Do not enter confined fire space without full bunker gear, including a SCBA.

6. Accidental release measures

Spill control: Avoid contact. Evacuate area. Eliminate ignition sources. Ventilate area.

Containment: Dike, contain, and absorb with clay, sand, or other suitable material.

Cleanup: For large spills, pump to storage/salvage vessels. Soak up residue with clay, sand, or other suitable material.

Special procedures: Prevent spill from entering drainage/sewer systems, waterways, and surface waters.

MATERIAL SAFETY DATA SHEET
MP54750 / MP54750NS PART A (RESIN)

7. Handling and storage

Handling precautions: Do not get in eyes, on skin or clothing. Wash with soap and water after using and particularly before eating, drinking, smoking, applying cosmetics, or using toilet facilities. Air dry and then launder contaminated clothing and protective gear before reuse. Close container after each use.

Storage: Keep in a cool, dry place. Keep containers closed when not in use. Keep away from open flames and high temperatures.

8. Exposure controls / personal protection

Eye and face protection: Wear safety glasses. Wear coverall chemical splash goggles when eye contact is possible.

Skin protection: Chemical-resistant gloves (i.e. butyl) and other gear as required to prevent skin contact. Respiratory

protection: No respiratory protection is usually required under normal conditions of use.

9. Physical and chemical properties

Specific gravity:	1.16	Boiling point:	> 150°C
Flash point:	> 100°C	Vapor pressure:	< 1 mbar @ 68°F

10. Stability and reactivity

This material is chemically stable. Hazardous polymerization will not occur.

Conditions to avoid: Avoid high temperatures.

Incompatible materials: Oxidizers, acids, and bases.

11. Toxicological information

Acute oral effects: LD50 > 2000 mg/kg

Acute dermal effects: LD50 > 2000 mg/kg

Sensitization: May cause skin sensitization.

Carcinogenicity: Recent 2-year bioassays in rats and mice exposed dermally yielded no evidence of carcinogenicity.

Mutagenicity: Resins of this type have proved to be inactive when tested by in vivo mutagenicity assays. These resins have shown activity in in vitro microbial mutagenicity screening and have produced chromosomal aberrations in cultured rat liver cells. The significance of these tests to man is unknown.

Inhalation effects: Not expected to be relevant, however, when exposure to vapors or mists is possible, it could cause respiratory tract irritation.

Skin effects: May be mildly irritating. May cause skin sensitization.

Eye effects: May be mildly irritating.

Ingestion effects: Not likely to be a relevant route of exposure.

12. Ecological information

Biodegradability: This section will be completed as ecological reviews are completed.

Toxicity to fish: This section will be completed as ecological reviews are completed.

13. Disposal considerations

Disposal: If this product becomes a waste, it would not be hazardous by RCRA criteria (40 CFR 261). Dispose of according to applicable federal, state, and local regulations.

14. Transport information

Not regulated for transport.

**MATERIAL SAFETY DATA SHEET
MP54750 / MP54750NS PART A**

15. Regulatory Information

TSCA: All components listed.

DSL: All components listed.

SARA Section 311/312 hazard classes: Chronic health hazard.

California Proposition 65: Contains Phenyl Glycidyl Ether (< 6 PPM), which was listed as carcinogenic on October 1st, 1990.

Risk Phrases: R36/38 – Irritating to eyes and skin

R43 – May cause sensitization by skin contact

R51/53 – Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

16. Other Information

No other information

NON-WARRANTY: Information contained herein is based on tests we believe to be reliable and accurate. It is offered in good faith for the benefit of the consumer. Adhesive Systems shall not be liable for any injury, loss, or damage in the use of its chemical products since the conditions of use are beyond our control. In every case we urge and recommend the user conduct tests to determine to their own satisfaction that the product is of acceptable quality and is suitable for their particular purpose under their own operating conditions. Statements concerning the possible use of our products are not intended as recommendations to use our products in the infringement of any patent. Because of changing reporting requirements and other variables it is impossible to guarantee the accuracy of the information contained in this document. It is the responsibility of the user to determine proper personal protection based on the actual condition of use and to comply with all Federal, State, and Local laws and regulations.

Engineering Excellence

For technical information

and support call **1-800-552-0299** or visit our website at

www.instantca.com

Revised
March 19th,
2013



9411 Corsair Road
Frankfort IL 60423
(800) 552-0299 Phone
(815) 464-5650 Fax

EMERGENCY PHONE (800) 255-3924
MATERIAL SAFETY DATA SHEET
MP54750/ MP 54750 NS PART B
(HARDENER)

HMIS	HEALTH 2	FLAMMABILITY 1	REACTIVITY 0
NFPA	HEALTH 2	FIRE HAZARD 1	REACTIVITY 0

1. Chemical Product

Product Name: MP54750 / MP54750NS Part B
(Hardener) Product Type: Curing Agent

2. Identity of Ingredients

Ingredients	CAS Number	%Composition
Polyaminoamide	68410-23-1	84-94
Triethylenetetramine	112-24-3	6-16

3. Hazards Identification

Human health hazards: May cause severe eye irritation. May cause severe irritation to the nose, throat, and respiratory tract. May be irritating to the skin. May cause skin sensitization. May cause respiratory tract sensitization.

Safety hazards: Not classified as flammable but will burn.

4. First aid measures

After inhalation: Fresh air. Give artificial respiration if not breathing. Get medical attention.

After skin contact: Rinse with running water for at least 15 minutes, remove contaminated clothing.

After eye contact: Rinse immediately with plenty of running water (for 15 minutes), seek medical attention.

After ingestion: Do not induce vomiting. Drink 1 glass of water unless victim is drowsy. Seek medical attention.

5. Fire-fighting measures

Suitable extinguishing media: Water fog, alcohol foam, extinguishing powder, CO2

Extinguishing media which must not be used for safety reasons: High pressure waterjet

Specific hazards during fire fighting: Material will not burn unless preheated. Cool containers with water.

6. Accidental release measures

Personal precautions: May burn although not readily ignitable. Shut off leaks if possible without personal risk.

Environmental precautions: Dike and contain. Do not allow large amounts to be released into drains or rivers.

Process for cleaning and take-up: Remove with liquid-absorbing material (sand, peat, sawdust)

7. Handling and storage

Handling: Ensure good ventilation/suction at the workplace, avoid open flames and sources of ignition

Storage: Ensure adequate ventilation. Store in a cool, dry place.

MATERIAL SAFETY DATA SHEET
MP54750 / MP54750NS PART B
(HARDENER)

8. Exposure controls / personal protection

Additional information for system design:	Ensure good ventilation/suction at the workplace
Hand protection:	Butyl gloves (BTT > 480 min) (In case of full contact) Nitrile gloves (BTT > 10 min) (In case of spray contact)
Eye protection:	Goggles which can be tightly sealed
General protection and hygiene measures:	Avoid skin and eye contact

9. Physical and chemical properties

State:	Amber liquid
Odor:	Aminic
Flash point:	>220°C (Open cup)
Density:	970 Kg/m ³
Viscosity (dynamic):	13,000 mPas

10. Stability and reactivity

Materials to avoid:	Vigorous reaction with strong oxidizing agents, and epoxy resins.
Dangerous decomposition products:	Nitrogen oxides and carbon monoxide.

11. Toxicological information

Basis for assesment:	Information given is based on a knowledge of the components and the toxicology of similar products.
Acute oral toxicity:	LD50 > 2000 mg/kg
Acute dermal toxicity:	LD50 > 2000 mg/kg
Eye irritation:	Expected to be an irritant
Skin irritation:	Expected to be an irritant

12. Ecological Information

General ecological information:	This section will be updated as ecological reviews are completed.
Other information:	Triethylenetetramine is resistant to biodegradation in biological waste water treatment plants. It could be toxic to the biomass in a treatment plant and could be toxic to fish.

13. Disposal considerations

Product disposal:	Place in an appropriate disposal facility in compliance with all regulations.
-------------------	---

14. Transport Information

Road transport ADR:	Not dangerous goods
Railroad transport RID:	Not dangerous goods
Inland water transport ADN:	Not dangerous goods
Marine transport IMDG:	Not dangerous goods
Air transport IATA:	Not dangerous goods

15. Regulatory information

DSL:	All components listed.
TSCA:	All components listed.
EINECS:	All components listed.

MATERIAL SAFETY DATA SHEET
MP54750 / MP54750NS PART B
(HARDENER)

16. Other Information

No other information.

NON-WARRANTY: Information contained herein is based on tests we believe to be reliable and accurate. It is offered in good faith for the benefit of the consumer. Adhesive Systems shall not be liable for any injury, loss, or damage in the use of its chemical products since the conditions of use are beyond our control. In every case we urge and recommend the user conduct tests to determine to their own satisfaction that the product is of acceptable quality and is suitable for their particular purpose under their own operating conditions. Statements concerning the possible use of our products are not intended as recommendations to use our products in the infringement of any patent. Because of changing reporting requirements and other variables it is impossible to guarantee the accuracy of the information contained in this document. It is the responsibility of the user to determine proper personal protection based on the actual condition of use and to comply with all Federal, State, and Local laws and regulations.