

# PLUG CONNECTORS FOR FOOD & BEVERAGE

## Connection cables

- M12 - M12
- Stainless Steel 1.4404 (V4A)
- Profile gasket

Approvals: 



**Male**  
straight

**Female**  
straight

**Male**  
straight

**Female**  
90°



<b>1 Form</b>	<b>40021</b>	<b>40121</b>
Type	4-pole	4-pole
Circuit diagram		
Contact layout		
<b>2 Cable Type</b>	<b>Jacket Color</b>	<b>Jacket Color</b>
Wire diameter 0.34 mm <sup>2</sup> PVC (UL/CSA)	gray 214	gray 214
<b>3 Cable Length</b>		
0.3 m	0030	
0.6 m	0060	
1.0 m	0100	
1.5 m	0150	
2.0 m	0200	
<b>Technical Data</b>		
Operating voltage	max. 250 V AC/DC	
Protection	IP65, IP67, IP68 inserted and tightened (EN 60529)	
Temperature range	-25...+85 °C	
<b>Article No.</b>		
The composition of your article number is explained on page 3.1.i	<b>7 0 1 4</b> - - - - -	
	<b>1 Form</b>	<b>2 Cable Type</b>
		<b>3 Cable Length</b>
<b>Notes</b>	Other versions on request. Further cable lengths on request.	

# PLUG CONNECTORS FOR FOOD & BEVERAGE

## Connection cables

- M12 - M12
- Stainless Steel 1.4404 (V4A)
- Profile gasket

Approvals: 

## Male

straight

## Female

90° with LED




## 1 Form

**40341**


### Type

4-pole with 3 × LED (PNP)  
(NPN) on request

### Circuit diagram



### Contact layout



## 2 Cable Type

### Jacket Color

Wire diameter 0.34 mm<sup>2</sup>  
PVC (UL/CSA)

gray  
214

## 3 Cable Length

0.3 m	0030
0.6 m	0060
1.0 m	0100
1.5 m	0150
2.0 m	0200

### Technical Data

Operating voltage	24 V DC ±25 %
Protection	IP65, IP67, IP68 inserted and tightened (EN 60529)
Temperature range	-25...+85 °C

### Article No.

The composition of your article number is explained on page 3.1.i

7 0 1 4

- 4 0 3 4 1 -

---

---

**1** Form

**2** Cable Type

**3** Cable Length

### Notes

Other versions on request. Further cable lengths on request.