

# VALVE CONNECTORS

SVS Eco

- Field-wireable
- Screw terminals
- without components

Approvals: 




**Form C (8 mm)**



**Form CI (9.4 mm)**

Industrial standard



| 1 Form  | 30055   | 30155   |
|---|---|---|
| Type  | 0...230 V AC/DC<br>without components<br>metric                                     | 0...110 V AC/DC<br>without components<br>metric                                       |
| Circuit diagram   |    |   |
| Contact figure  | Cable outlet can be turned in 90° steps   |   |
| Contact layout  |  |  |
| <b>Technical Data</b>   |   |   |
| Operating voltage   | 0...230 V AC/DC   | 0...110 V AC/DC   |
| Operating current per contact                                     | max. 6 A  |   |
| Connection cross section  | 0.34...0.5 mm <sup>2</sup>  |   |
| Sealing range (cable diameter)                                    | 4...6 mm  |   |
| Locking of ports  | M2.5 (couple de serrage recommandé 0,4 Nm)  | M3 (recommended torque 0.4 Nm)  |
| Contact figure  | Cable outlet can be turned in 90° steps   |   |
| Compression gland   | M16 × 1.5 mm  | M12 × 1.75 mm   |
| Protection  | IP65 inserted and tightened   |   |
| Temperature range   | -40...+80 °C  |   |
| <b>Article No.</b>  |   |   |
| The composition of your article number is explained on page 3.1.i | <u>7 0 0 0</u> - _____ - <u>0 0 0</u>   | <u>0 0 0 0</u>  |
|   | <b>1 Form</b>   |   |
| Notes   | Other versions on request.  |   |