

## VALVE CONNECTORS

SVS Eco, LED

– Field-wireable

– Screw terminals


Approvals: 

Form A (18 mm)



1 Form	29005	29085	29165
Type	24 V AC/DC	110 V AC/DC	230 V AC/DC
	LED and VDR	LED and VDR	LED and VDR
	metric	metric	metric


Circuit diagram



Contact figure

Cable outlet can be turned in 90° steps

Contact layout



### Technical Data

Operating voltage	24 V AC/DC ±10 %	110 V AC/DC ±10 %	230 V AC/DC ±10 %
Operating current per contact	max. 1.5 A		
Connection cross section	0.5...1.5 mm²		
Sealing range (cable diameter)	6...8 mm		
Locking of ports	M3 (recommended torque 0.4 Nm)		
Compression gland	M16 × 1.5 mm		
Contact figure	Cable outlet can be turned in 90° steps		
Protection	IP65 inserted and tightened		
Temperature range	-40...+60 °C		

### Article No.

The composition of your article number is explained on page 3.1.i

7 0 0 0

- - - - -

0 0 0

0 0 0 0

1 Form


Notes

Other versions on request.

SVS Eco, LED



– Field-wireable

– Screw terminals

Approvals: 

Form B (10 mm)




1	Form	29565	29645	29685
	Type	24 V AC/DC	110 V AC/DC	230 V AC/DC
		LED and VDR	LED and VDR	LED and VDR
		metric	metric	metric
	Circuit diagram			
	Contact figure	Cable outlet can be turned in 180° steps		
	Contact layout			
Technical Data				
	Operating voltage	24 V AC/DC ±10 %	110 V AC/DC ±10 %	230 V AC/DC ±10 %
	Operating current per contact	max. 1.5 A		
	Connection cross section	0.5...1.5 mm²		
	Sealing range (cable diameter)	6...8 mm		
	Locking of ports	M3 (recommended torque 0.4 Nm)		
	Compression gland	M16 × 1.5 mm		
	Contact figure	Cable outlet can be turned in 180° steps		
	Protection	IP65 inserted and tightened		
	Temperature range	-40...+60 °C		
Article No.				
	The composition of your article number is explained on page 3.1.i	<div><div><div>7</div><div>0</div><div>0</div><div>0</div></div><div>-</div><div><div></div><div></div><div></div><div></div><div></div><div></div></div><div>-</div><div><div>0</div><div>0</div><div>0</div></div><div></div><div><div>0</div><div>0</div><div>0</div><div>0</div></div></div>		
		<div>1</div> Form		
Notes				
	Other versions on request.			

## VALVE CONNECTORS

SVS Eco, LED

– Field-wireable

– Screw terminals

Approvals: 


Form BI (11 mm)

Industrial standard



1 Form	29805	29885	29925
Type	24 V AC/DC	110 V AC/DC	230 V AC/DC
	LED and VDR	LED and VDR	LED and VDR
	metric	metric	metric


Circuit diagram



Contact figure

Cable outlet can be turned in 180° steps

Contact layout



### Technical Data

Operating voltage	24 V AC/DC ±10 %	110 V AC/DC ±10 %	230 V AC ±10 %
Operating current per contact	max. 1.5 A		
Connection cross section	0.5...1.5 mm²		
Sealing range (cable diameter)	6...8 mm		
Locking of ports	M3 (recommended torque 0.4 Nm)		
Compression gland	M16 × 1.5 mm		
Contact figure	Cable outlet can be turned in 180° steps		
Protection	IP65 inserted and tightened		
Temperature range	-40...+60 °C		

### Article No.

The composition of your article number is explained on page 3.1.i

7 0 0 0

- - - - -

0 0 0

0 0 0 0

1 Form

Notes


Other versions on request.

# | VALVE CONNECTORS

SVS Eco, LED



– Field-wireable

– Screw terminals

Approvals: 

Form C (8 mm)



1 Form	30105	30115	30125
Type	24 V AC/DC	110 V AC/DC	230 V AC/DC
	LED and VDR	LED and VDR	LED and VDR
	metric	metric	metric
Circuit diagram			
Contact figure	Cable outlet can be turned in 90° steps		
Contact layout			
Technical Data			
Operating voltage	24 V AC/DC ±10 %	110 V AC/DC ±10 %	230 V AC/DC ±10 %
Operating current per contact	max. 1.5 A		
Connection cross section	0.34...0.5 mm²		
Sealing range (cable diameter)	4...6 mm		
Locking of ports	M2.5 (couple de serrage recommandé 0,4 Nm)		
Compression gland	M12 × 1.75 mm		
Contact figure	Cable outlet can be turned in 90° steps		
Protection	IP65 inserted and tightened		
Temperature range	-40...+60 °C		
Article No.			
The composition of your article number is explained on page 3.1.i	<div><div><div>7</div><div>0</div><div>0</div><div>0</div></div><div>-</div><div><div></div><div></div><div></div><div></div></div><div>-</div><div><div>0</div><div>0</div><div>0</div></div><div><div>0</div><div>0</div><div>0</div><div>0</div></div></div>		
	1 Form		
Notes			
Other versions on request.			

## VALVE CONNECTORS

SVS Eco, LED

– Field-wireable

– Screw terminals

Approvals: 

Form CI (9.4 mm)

Industrial standard



### 1 Form

30205

30215

Type

24 V AC/DC

110 V AC/DC


LED and VDR

LED and VDR

metric

metric


Circuit diagram



Contact figure

Cable outlet can be turned in 90° steps

Contact layout



### Technical Data

Operating voltage	24 V AC/DC ±10 %	110 V AC/DC ±10 %
Operating current per contact	max. 1.5 A	
Connection cross section	0.34...0.5 mm²	
Sealing range (cable diameter)	4...6 mm	
Locking of ports	M3 (recommended torque 0.4 Nm)	
Compression gland	M12 × 1.75 mm	
Contact figure	Cable outlet can be turned in 90° steps	
Protection	IP65 inserted and tightened	
Temperature range	-40...+60 °C	

### Article No.

The composition of your article number is explained on page 3.1.i

7 0 0 0

-

\_\_\_\_\_

0 0 0

0 0 0 0

1 Form

Notes

Other versions on request.