



7180

THORO-SPRAY® High Pressure Spray Hose – 800 PSI Series 7180

Designed for agricultural and residential high pressure spray applications. The tube will handle most pesticides as well as liquid fertilizers. The cover is non-marking for safe use in residential areas.

4:1 Design factor

>> Non-marking cover

| | |
|--------------------------|--|
| Tube | Black Nitrile |
| Cover | Green Nitrile/PVC |
| Reinforcement | Multiple textile braids |
| Temperature Range | -20° F to +180° F (-29°C to +82°C) |
| Branding | PARKER USA 7180 THORO-SPRAY® HOSE - 800 PSI MAX WP |
| Brand Description | Ink Brand - Black letter color |
| Compare to | Goodyear Pliovic Ag Spray; Gates Thermo AG800 |

LENGTHS: Random lengths on nominal 500 ft. reels, 5 piece maximum with 50 ft. minimum length.

COUPLINGS: For permanent crimp specifications, refer to CrimpSource. Other available coupling options: Series 7615, 7692. For assembly guidelines and additional coupling options, refer to NAHAD Industrial Hose Assembly Guidelines.

| Part No. | ID (in.) | ID (mm) | Reinf. Braids | OD (in.) | OD (mm) | Approx. Wt. Per 100 Ft. | Min. Bend Radius | Max. Rec. WP |
|----------|----------|---------|---------------|----------|---------|-------------------------|------------------|--------------|
| 7180-252 | ¼ | 6.4 | 2 | 0.625 | 15.9 | 15 | 3.0 | 800 |
| 7180-382 | ⅜ | 9.5 | 2 | 0.750 | 19.1 | 20 | 4.0 | 800 |
| 7180-502 | ½ | 12.7 | 2 | 0.938 | 23.8 | 29 | 5.0 | 800 |
| 7180-752 | ¾ | 19.1 | 2 | 1.250 | 31.8 | 48 | 6.5 | 800 |

Applications

- Fertilizers
- Pesticide Sprayers