

SUPER-FLEX® EPDM Heavy Duty Water Suction Hose

Series 7325

Series 7325 is a heavy duty, high pressure suction and discharge hose designed to handle alkalies, brine, glycols, herbicides, mild chemicals, slurries and water. The hose construction incorporates a wire helix that provides full suction capability and kink resistance, with a heavy wall and elevated working pressure for durability and superior service. The EPDM cover is resistant to abrasion, heat, mild chemicals and weathering. Series 7325 is available in 200-foot continuous lengths.

Tube: Black EPDM

Reinforcement: Multiple textile plies with wire helix
Cover: Black EPDM; wrapped finish

Temp. Range: $-40^{\circ}\text{F to } +212^{\circ}\text{F } (-40^{\circ}\text{C to } +100^{\circ}\text{C})$

Brand Method: White text on blue stripe

Brand Example: PARKER SERIES 7325 HD WATER SUCTION 300 PSI MAX WP

MADE IN USA

Design Factor: 4:1

Industry Standards: None applicable

Applications: • Alkalies, brine, glycols, herbicides, mild chemicals, slurries, water

· Agriculture, construction, general industrial, irrigation surface mining

Vacuum: Full **Packaging:** Coils

Part Number	ID (in)	ID (mm)	Reinf Plies	OD (in)	OD (mm)	Approx Wt (lbs/ft)	Approx Wt (kg/ft)	Min Bend Rad (in)	Min Bend Rad (mm)	Max Rec WP (psi)	Max Rec WP (bar)	Perm Cplg Rec *	Std Pack Qty (ft)	Stock Status **
7325-1500	1-1/2	38.1	4	2.094	53.2	1.07	0.48	6.0	152.4	300	20.7	*	100	Υ
7325-2000	2	50.8	4	2.661	67.6	1.53	0.69	8.0	203.2	300	20.7	*	100	Υ
7325-2500	2-1/2	63.5	4	3.228	82.0	2.11	0.96	10.0	254.0	300	20.7	TM	100	Υ
7325-3000	3	76.2	4	3.700	94.0	2.39	1.08	12.0	304.8	300	20.7	*	100	Ν

^{*} Couplings: Refer to CrimpSource at www.safehose.com for coupling recommendations and crimp specifications.

⚠ WARNING! Couplings attached with bands or clamps may reduce the working pressure of the hose assembly to less than the maximum rated working pressure of the hose. Refer to the NAHAD Industrial Hose Assembly Guidelines.



^{**} Stock: "Y" indicates stocked item; "N" indicates non-stocked item. Stock status subject to change. Contact Parker Customer Service.