



Parker Hannifin Corporation
Industrial Hose Division
30242 Lakeland Boulevard
Wickliffe, OH 44092-1747

Telephone: (440) 833-2120
Fax: (440) 833-2230
www.safehose.com

Sales Advisory



PRODUCT UPDATE

WILDCATTER® PROGRAM

Series SW360 Wildcatter Hot Air Blower Hose

Update to Hose Brand/Layline; Additional Crimp Specs



Series SW360 is a heavy duty, high pressure hot air blower hose designed for bulk loading/unloading of dry materials in plants or oilfield service vehicles, such as dry cement haulers. The hose transfers hot air from a compressor to the storage bin/cargo bay to propel bulk product. The hose construction incorporates a tube that features a temperature rating to 350°F (177°C) and resists drying out. The dual wire helix provides full suction capability, kink resistance, flexibility for ease of handling and a path to conduct a static electrical charge to ground. The cover resists abrasion, heat and ozone.

The Wildcatter trade name indicates the product is designed and manufactured for premium service in oilfield applications. However, Wildcatter products may be used in other industries, markets and applications where the product meets the required performance criteria.

(Continued on page 2)

If there are any questions please contact
Parker Customer Service toll-free at:

866.810.HOSE (4673)
Wickliffe, OH
Eastern USA

800.242.HOSE (4673)
South Gate, CA
Western USA





Parker Hannifin Corporation
Industrial Hose Division

Sales Advisory

Page 2

Series SW360 Wildcatter Hot Air Blower Hose *Update to Hose Brand/Layline; Additional Crimp Specs*

Tube:	Black EPDM
Reinforcement:	Multiple textile plies with dual wire helix
Cover:	Black EPDM; wrapped finish
Temp Range:	-40°F to +350°F (-40°C to +177°C)
Brand Method:	Black text on yellow stripe
Brand Example:	PARKER WILDCATTER SW360 HOT AIR BLOWER HOSE XXX MAX WP MADE IN USA
Design Factor:	4:1
Industry Standards:	None applicable
Applications:	<ul style="list-style-type: none"> • Hot air blower systems • In-plant transfer; delivery, loading/unloading • General industrial, oilfield, transportation
Vacuum:	Full
Packaging:	Coils

Crimp Specifications

For currently qualified crimp specifications including coupling designation, refer to CrimpSource at www.safehose.com.
Refer to the COS-K4 crimper for crimp specs for hose 4" ID and smaller. Refer to the COS-K6 or COS-K10 crimpers for hose IDs larger than 4".

Part Number	ID (in)	ID (mm)	Reinf Plies	OD (in)	OD (mm)	Approx Wt (lbs/ft)	Approx Wt (kgs/ft)	Min Bend Rad (in)	Min Bend Rad (mm)	Max Rec WP (psi)	Max Rec WP (bar)	Std Pack Qty (ft)	Stock Status **
SW360-2000	2	50.8	2	2.500	63.5	1.08	27.40	6.0	152.4	200	13.8	100	Y
SW360-3000	3	76.2	2	3.563	90.5	1.78	45.20	12.0	304.8	200	13.8	100	Y
SW360-4000	4	101.6	2	4.563	115.9	2.46	62.50	16.0	406.4	125	8.6	100	Y
SW360-6000	6	152.4	2	6.813	173.0	5.00	127.00	24.0	609.6	100	6.9	100	Y

** **Stock:** "Y" indicates stocked item; "N" indicates non-stocked item. Stock status subject to change. Contact Parker Customer Service.

⚠ WARNING! Couplings attached with bands or clamps may reduce the working pressure of the hose assembly to less than the maximum rated working pressure of the hose. Refer to the NAHAD Industrial Hose Assembly Guidelines.