## SS290 BEVERAGE AND POTABLE WATER HOSE - NITRILE TUBE

- Lightweight, sanitary discharge hose designed to handle a wide variety of food and beverage transfer applications.
- Excellent C.I.P. cleaning hose for overhead units.
- Manufactured on stainless steel mandrels for an ultra-smooth bacteria free tube that will not impart taste or odor.

Tube:	Extruded white Nitrile.
Reinforcement:	Textile.
Cover:	Gray specially compounded Natural Rubber.
Temperature:	-40° to +160°F.

I.D.	0.D.	REINFORCEMENT	WORKING PRESSURE PSI	WEIGHT LB/FT
<b>1</b> <sup>1</sup> /2"	<b>2</b> <sup>1</sup> /8"	4 plies	250	.82
2"	<b>2</b> <sup>5</sup> /8"	4 plies	250	1.10
<b>2</b> <sup>1</sup> /2"	<b>3</b> <sup>1</sup> /8"	4 plies	250	1.39
3"	<b>3</b> <sup>5</sup> /8"	4 plies	250	1.64
4"	<b>4</b> <sup>5</sup> /8"	4 plies	250	2.21

## SW319 FOOD SUCTION HOSE - EPDM TUBE

- Premium quality, high temperature food hose designed for sanitary suction and hot air blower service in food applications.
- Dual helix design offers full vacuum capabilities.
- Lightweight construction offers excellent flexibility for handling ease.
- Manufactured on stainless steel mandrels for an ultra-smooth bacteria free tube that will not impart taste or odor.

Tube:	Extruded white EPDM.
Reinforcement:	Textile with dual wire helix.
Cover:	Gray EPDM.
Temperature:	-20° to +225°F

I.D.	0.D.	BEND RADIUS	WORKING Pressure psi	WEIGHT LB/FT	VACUUM
<b>1</b> <sup>1</sup> /4"	<b>1</b> <sup>13</sup> /16"	5"	250	.75	Full
<b>1</b> <sup>1</sup> /2"	<b>2</b> <sup>1</sup> /16"	6"	250	.86	Full
2"	<b>2</b> <sup>5</sup> /8"	7"	200	1.27	Full
<b>2</b> <sup>1</sup> /2"	<b>3</b> <sup>3</sup> /16"	10"	200	1.75	Full
3"	<b>3</b> <sup>11</sup> /16"	12"	150	2.25	Full

## SW330 SANITARY SUCTION & DISCHARGE HOSE - CHLOROBUTYL TUBE


- Premium quality sanitary suction and discharge hose designed to handle non-oily food products.
- Seamless extruded tube is highly resistant to C.I.P. solutions, microbes, and bacteria.


Tube:	Extruded white Chlorobutyl.			
<b>Reinforcement:</b>	Textile with dual wire helix.			
Cover:	Gray EPDM.			
Temperature:	-40° to +225°F.			

I.D.	0.D.	BEND RADIUS	WORKING PRESSURE PSI	WEIGHT LB/FT	VACUUM
1"	<b>1</b> <sup>5</sup> /8"	4"	150	.75	Full
<b>1</b> <sup>1</sup> /2"	<b>2</b> <sup>3</sup> /16"	6"	150	1.05	Full
2"	<b>2</b> <sup>5</sup> /8"	7"	150	1.45	Full
<b>2</b> <sup>1</sup> / <sub>2</sub>	<b>3</b> <sup>1</sup> /4"	8"	150	1.92	Full
3"	<b>3</b> <sup>3</sup> /4"	9"	150	2.47	Full
4"	<b>4</b> <sup>3</sup> /4"	12"	150	3.25	Full

Meets FDA, USDA, 3A, and PMO sanitary requirements.







Meets FDA, USDA, 3A, and PMO sanitary requirements. Microbe and bacteria resistant tube.

