


SW630 TITANFLEX® FOOD SUCTION HOSE - WHITE CHLOROBUTYL TUBE

- Ultra-flexible food hose designed for milk, fruit juices, soft drinks, beer, wine, pharmaceuticals, cosmetics, and other non-oily food products.
- Smooth cover provides extreme flexibility while minimizing bacteria build-up often found in corrugated hoses.
- Cleans easily with hot water, 10% alkali bath, or open-end low pressure steam up to 15 psi.
- Manufactured on stainless steel mandrels for an ultra-smooth bacteria free tube that will not impart taste or odor.

Meets FDA, USDA, 3A, and PMO sanitary requirements.



Tube: Extruded white Chlorobutyl.
Reinforcement: Textile with dual wire helix.
Cover: Gray EPDM.
Temperature: -40° to +225°F.

I.D.	O.D.	BEND RADIUS	WORKING PRESSURE PSI	WEIGHT LB/FT	VACUUM
1½"	2½"	4½"	200	.98	Full
2"	2¼"	6"	200	1.37	Full
2½"	3½"	7½"	200	1.77	Full
3"	3¾"	9"	200	2.23	Full
4"	4¾"	12"	200	3.18	Full

TITANFLEX® is a registered trademark of Titan Industries.



SWC430 CORRUGATED FOOD GRADE SUCTION - NITRILE TUBE

- Corrugated sanitary suction hose designed for oily foods and multi-purpose food transfer applications.
- Dual helix design provides full vacuum capabilities.
- Abrasion resistant cover provides excellent protection against oily foods, mild chemicals, and ozone attack.
- Manufactured on stainless steel mandrels for an ultra smooth bacteria free tube that will not impart taste or odor.

Meets FDA, USDA, 3A, and PMO sanitary requirements.

Tube: Extruded white Nitrile.
Reinforcement: Textile with dual wire helix.
Cover: Gray corrugated Nitrile.
Temperature: -20° to +225°F

I.D.	O.D.	BEND RADIUS	WORKING PRESSURE PSI	WEIGHT LB/FT	VACUUM
2"	2⅝"	5"	150	1.46	Full
3"	3⅞"	6"	150	2.39	Full
4"	4⅜"	8"	150	3.68	Full
6"	6¾"	12"	100	5.86	Full



SWC432 SANIFLEX CORRUGATED FOOD SUCTION - NITRILE TUBE

- Ultra-flexible food suction and discharge hose designed for oily foods and a variety of food transfer applications.
- Smooth enhanced corrugations allow easy sanitary cleaning.
- Nitrile cover is ozone, abrasion, chemical and oil resistant.
- Manufactured on stainless steel mandrels for an ultra-smooth bacteria free tube that will not impart taste or odor.

Meets FDA, USDA, and 3A sanitary requirements.

Smooth enhanced corrugated cover allows easy sanitary cleaning.

Tube: Extruded white Nitrile.
Reinforcement: Textile with dual wire helix.
Cover: Gray Nitrile.
Temperature: -40° to +225°F.

I.D.	O.D.	BEND RADIUS	WORKING PRESSURE PSI	WEIGHT LB/FT	VACUUM
2"	2⅞"	5"	200	1.33	Full
3"	3⅝"	8"	150	2.09	Full
4"	4⅞"	10"	100	3.11	Full

