



Product Group:	Air Preparation	Actuators	Cylinders	Grippers	Vacuum / Sensors	Valves	Other
<b>Notice of Product Change</b>							
Subject:	<b>P31RB Reverse Flow</b>						

PDN announces a change to the new “B” engineering level P31R and P31H regulators. At launch in December 2014, it was stated that P31 regulators were reverse flow as standard. That statement is inaccurate. The P31RB and P31HB series must be called out with the “R” reverse flow designator in the ordering code. Only the P32R and P32H are reverse flow as standard. Please accept our sincerest apologies for any inconvenience this may have caused you or your customers.

**P31RB 9 2 B N N P**

<b>Basic series</b> Global modular mini regulator P31RB	<b>Thread type</b> BSPP 1 BSPT 2 NPT 9	<b>Port size</b> 1/4 2	<b>Relief</b> Relieving B Non-relieving N <b>Reverse flow-relieving R</b>	<b>Mounting</b> P Plastic panel mount nut	<b>Adjustment range</b>																																												
					<table border="1"> <thead> <tr> <th colspan="2">With square gauge</th> <th colspan="2">With round gauge</th> </tr> <tr> <th>psig</th> <th>bar</th> <th></th> <th></th> </tr> </thead> <tbody> <tr> <td>1 = 30*</td> <td>V = 2*</td> <td>Z</td> <td>2 bar; 30 psig; 0.2 MPa</td> </tr> <tr> <td>3 = 60</td> <td>S = 4</td> <td>M</td> <td>4 bar; 60 psig; 0.4 MPa</td> </tr> <tr> <td>5 = 125</td> <td>T = 8</td> <td>G</td> <td>8 bar; 125 psig; 0.8 MPa</td> </tr> <tr> <td></td> <td></td> <td>J</td> <td>16 bar; 232 psig; 1.6 MPa</td> </tr> <tr> <td colspan="4" style="text-align: center;"><b>Without gauge</b></td> </tr> <tr> <td></td> <td></td> <td>Y</td> <td>2 bar; 30 psig; 0.2 MPa</td> </tr> <tr> <td></td> <td></td> <td>L</td> <td>4 bar; 60 psig; 0.4 MPa</td> </tr> <tr> <td></td> <td></td> <td>N</td> <td>8 bar; 125 psig; 0.8 MPa</td> </tr> <tr> <td></td> <td></td> <td>H</td> <td>16 bar; 232 psig; 1.6 MPa</td> </tr> </tbody> </table>	With square gauge		With round gauge		psig	bar			1 = 30*	V = 2*	Z	2 bar; 30 psig; 0.2 MPa	3 = 60	S = 4	M	4 bar; 60 psig; 0.4 MPa	5 = 125	T = 8	G	8 bar; 125 psig; 0.8 MPa			J	16 bar; 232 psig; 1.6 MPa	<b>Without gauge</b>						Y	2 bar; 30 psig; 0.2 MPa			L	4 bar; 60 psig; 0.4 MPa			N	8 bar; 125 psig; 0.8 MPa			H	16 bar; 232 psig; 1.6 MPa
With square gauge		With round gauge																																															
psig	bar																																																
1 = 30*	V = 2*	Z	2 bar; 30 psig; 0.2 MPa																																														
3 = 60	S = 4	M	4 bar; 60 psig; 0.4 MPa																																														
5 = 125	T = 8	G	8 bar; 125 psig; 0.8 MPa																																														
		J	16 bar; 232 psig; 1.6 MPa																																														
<b>Without gauge</b>																																																	
		Y	2 bar; 30 psig; 0.2 MPa																																														
		L	4 bar; 60 psig; 0.4 MPa																																														
		N	8 bar; 125 psig; 0.8 MPa																																														
		H	16 bar; 232 psig; 1.6 MPa																																														
				<b>Adjustment</b> N Non-rising knob	* Unit comes with 0-4 bar or 0-60 psig gauge respectively.																																												

**Bold items are most common.**

- The Product(s) Shown Above Have Been Approved for Change Effective:..... February 26, 2015
- Orders for Complete Units Will Be Accepted Until ..... N/A
- Orders for Kits Will Be Accepted Until ..... N/A
- Last Date Returns Accepted ..... N/A



Parker Hannifin Corporation  
**Pneumatic Division**  
8676 E. M89  
P.O. Box 901  
Richland, MI 49083 USA  
Tel: 269 629 5000  
Fax: 269 629 5385

Applications Engineering  
Phone: 877 321 4PDN Option #2  
E-mail: pdnapps@parker.com  
Customer Support  
Phone: 877 321 4PDN Option #1  
E-mail: pdncustsvc@parker.com  
Web site: www.parker.com/pneumatics